



Description:

It is an HDMI switcher which supports 4K ultra HD video; support 4 HDMI inputs and 4 HDMI outputs.

Feature:

- * Support 4 HDMI inputs, 4 HDMI outputs.
- * Support HDMI 1.4 standard, HDCP1.4 standard.
- * HDMI input supports simultaneous audio and video input; it has 4 audio output interfaces, which can be connected to external mixers, processors, active
- speakers and other equipment for reinforcent.

 * The maximum input and output resolution 3840x2160@30Hz, which is compatible with any resolution no bigger than the maximum resolution, and the output resolution is consistent with the input resolution.

 * DC 12V power supply, the maximum power consumption is 20W.

Specification:

Model	TS-9104UHM
Digital video input	4×HDMI Digital video input
Output interface	4×HDMI Digital video Output, 4×analog audio output port
Control interface	1×NETWORK,1×RS 232,1×IR IN,1×USB UPDATE
HDMI	HDMI1.4
HDCP	HDCP1.4
HDMI maximum bandwidth	10.2Gbps
Maximum transmission distance	10m(3840×2160(30Hz));15 m(1080P(60Hz))
Environment temperature	-10°C—+45°C
Ambient humidity	10%-80%
Power supply	DC 12V
Power consumption	20W
Dimension(L*W*H)	484*298*45mm
Weight	3.5Kg