



## Feature:

- \* Unique patented technology; with anti-RF tube to prevent noise and secure a perfect conference environment. \* Unique patented appearance, delicate and modernize.
- \* Special microphone head design, even without cotton cover, it can also eliminate the low frequency impact sound.
- \* Professional heart-shaped capacitor microphone core; with high sensitivity and clear voice; with red and green annular indicator light.

- \* Red indicator light means MIC is on; green indicator light means applying for talking.
  \* With feedback function. When microphone on, built-in speaker will be off.
  \* Built-in speaker and earphone jack, earphone volume is adjustable.
  \* The unit cascade with a professional 8-pin aviation plug with a metal fixed nut, which will not loosen or fall off.
  \* The unit comes with a 1.8-meter wire, and the wire is shielded by full-line aluminum foil + waterline, which greatly reduces the interference of strong electromagnetic waves on the wire to avoid noise.
- \* The address code of each unit can be adjusted freely at any time to facilitate construction.
  \* Mic units power supplied by conference controller, 24V DC, safety use.
  \* Chairman unit is not limited by numbers when talking.

- \* Chairman unit has the priority right to control delegate unit.
- \* Chairman unit position is no limited, it can be placed anywhere according to user demands. \* Hand in hand connection, easy for installation and maintenance.

## **Specifications:**

Model	TS-0621
Microphone Type	Cardioid directional electret
Frequency Response	80Hz~16KHz
MIC Input Impedance	1ΚΩ
Sensitivity	-34±2dB(0dB=1V/Pa,at 1kHz)
Max SPL	100dB(THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Consumption	2W
Earphone Load	8-32Ω
Earphone Volume	Max 40mW
Earphone Jack	3.5mmMono jack
Standard	IEC60914
Connector	1.8m Aviation 8 core
Power Supply Mode	DC24V
Color	Silver
Weight	0.9kg
Microphone Length	409mm
Dimension(mm)	225(L)×131(W)×48(H)
Mounting	Desktop