



Feature

- * Capacitive touch keys are adopted to ensure no key tapping sound and a good environment of the venue.
- * Uncompressed audio transmission technology. The sampling rate is up to 48K, and it can provide perfect sound quality with a bandwidth of 80Hz-16KHz.
- * It adopts 100M network transmission. And the network connection adopts network cable hand in hand, which is convenient for wiring.
- * Communication adopts standard TCP/IP protocol, and each unit can support ping packet function.
- * 4.3-inch full-color touch screen.
- * Simultaneous interpretation supports 63+1 channels, and the unit has a dual-channel listening function, which can listen to different interpreter channels at the same time.
- * The unit supports microphone control and voice control function by PC software.
- * The chairman unit has the priority right to turn off the speaking of the delegate unit.
- * Each unit has a built-in independent web server. Support four language switching, adjustment of microphone ID number, microphone sensitivity, microphone EQ and other parameters
- * It has the function of speech countdown and speech timekeeping, and the delegate unit can apply for speaking.
- * Internal feedback suppression function, voice control function, adjustable voice control sensitivity.
- * With a 5-band EQ adjustment function. Different sound effects can be adjusted according to the voice characteristics of the speaker until the perfect effect is achieved.
- * Support voting function. There are multiple voting mode options, and the content of the options can be customized and sent to the unit for display.
- * Support sign-in function. You can also disable and control the unit check-in, and other functions through the PC software.
- * Support firmware upgrade function on the web page.
- * Support the IP address sniffing function. And the ID number, IP address, MAC address and other parameters of the unknown unit can be found through the PC tool.

Specification

Model	TS-0310
Microphone type	Electret capacitive
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	1KΩ
Sensitivity	-36±1.5dB(0dB=1V/Pa, at1KHz)
Maximum SPL	120dB(THD>3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
MAX power consumption	4.5W
Standard	IEC60914
Power supply	Conference controller
Color	Sand graphite gray
Sign in	Key
Dimension (LxWxH)	140×136×49mm
Installation method	Desktop
Weight	0.70Kg