



Line Array Speaker

TK-L205/TK-S125



Description:

*Made of high-quality plywood, the cabinet is characterized by small size, light weight, and wear-resistant spray paint treatment.

*It is composed of two 5" neodymium magnet mid-woofer units and one 1.73" neodymium magnet tweeter driver with high sensitivity.

*The precisely designed crossover optimizes the power response and the mid-frequency expressiveness of the vocal part.

*The hoisting combined linear array design allows the speaker coverage area to be adjusted in the range of 0-10 degrees.

*The combination of professional pendant parts, simple and quick pendant method, easy to assemble in sound engineering.

*With a wide range of applications, it works with TA professional amplifiers and audio processors. It is suitable for reinforcement in conference rooms, multi-function halls, and banquet halls.

Specification:

Model	TK-L205
Type	2-channel linear array speaker
Rated power	200W
Peak power	800W
Nominal impedance	8Ω
Frequency range	65Hz-20KHz
Sensitivity	100dB
Woofer	5"woofer*2
Tweeter	1.73" compressed driver*1
Horizontal coverage angle (-6dB)	120°
Vertical coverage angle (-6dB)	10°
Weight	9.2kg
Dimension (H×W×D)	(167+118)×455×315mm

Model	TK-S125
Type	Subwoofer
Power	500W
Peak power	2000W
Nominal impedance	8Ω
Frequency range	45Hz-500Hz
Sensitivity	99dB
Woofer	12"*1
Weight	20kg
Dimension (H×W×D)	360×455×400mm